


EDGE PROTECTION WITH FABRIC



> alkali resistant

Product description

Plastic edge profile with fine alkali-resistant glass fibre fabric. Can be used as corner reinforcement.

Delivery format

Container	Outer packaging	Pallet
50 STK / STK	50	2000 STK

Storage

Can be stored frost-free, cool, and dry on wooden shelves in the unopened original container for 0 days

Processing

Processing

The adherence to the processing guidelines as well as the proper and professional execution of all connections and terminations are essential for the functional, practical, optical and lasting success of WDV systems. This ensures that stresses as a result of the weather (sun, wind, rain and snow) and the type of construction (building dynamics, building physics) do not adversely affect the life of the facade.

Our consultants will be happy to provide you with detailed and building-specific information!

Product and processing instructions

Material information:

- The properties of the material may be significantly altered if not processed within the ideal temperature and/or humidity range.
- Bring the materials to the proper temperature before processing!
- To maintain the product properties, do not add any foreign materials!
- Water dosing quantities or dilution information must be strictly adhered to!
- Check tinted products for colour accuracy before application!
- Colour consistency can only be guaranteed within the same batch.
- The environmental conditions significantly impact colour formation.

Environmental instructions:

- Do not process at temperatures below +5°C!
- The ideal temperature range for the material, substrate and air is +15°C to +25°C.
- The ideal humidity range is 40% to 60% relative humidity.

55110, EDGE PROTECTION WITH FABRIC, valid from: 11.07.2024, Nicole Zeiml, Page 1

Colour technology

- Increased air humidity and/or lower temperatures may prolong the drying, setting and hardening time, while lower air humidity and/or higher temperatures will speed it up.
- Ensure adequate ventilation during the drying, reaction and hardening phases; avoid draughts!
- Protect against direct sunlight, wind, and weather!
- Protect adjacent components!

Tips:

- We recommend using a test surface first or a small area for initial, small-scale testing.
- Please heed the product data sheets of all MUREXIN products used in the process.
- Keep a genuine original container of the respective batch for later repair work.

The information provided reflects average values that were obtained under laboratory conditions. Due to the use of natural raw materials, the indicated values of individual deliveries may vary slightly without impacting the product suitability.

Safety instructions

This leaflet is based on extensive experience, is intended to convey the best of our knowledge, is not legally binding and does neither constitute a contractual legal relationship nor a subsidiary obligation resulting from the bill of sale. The quality of our materials is guaranteed within the framework of our general terms and conditions. Our products may be used by professionals and/or experienced and accordingly technically skilled persons only. Users are not released from inquiring in case of uncertainties or from rendering professional workmanship. We recommend using a test surface first or a small area for initial, small-scale testing. Naturally, it is not possible to describe or foresee all possible current and future uses and peculiarities. Information that is assumed to be familiar to experts has been omitted.

Please observe the current, technical, national and European standards, guidelines and data sheets regarding materials, substrates and the subsequent construction. Please contact us if you have any reservations or doubt.

This version is rendered invalid if a new version is released. The most recent data sheets, safety data sheets and the terms and conditions are available online at www.murexin.com.